O NORTH MARIN WATER DISTRICT

2019 ANNUAL WATER QUALITY REPORT · NOVATO EDITION · PUBLISHED JUNE 2020

Water served by North Marin Water District to its customers comes from protected watersheds and is purified using modern treatment techniques to remove pathogens, including bacteria and viruses. Water is continuously monitored to ensure that it surpasses all state and federal standards for health and safety.

This brochure is a snapshot of water quality monitoring performed in 2019. Included are details about where your water comes from, what it contains, and how it compares to regulatory standards. As you make any preparations to deal with the risks of coronavirus (COVID-19) you can feel confident that your tap remains a safe and reliable source of clean, good-tasting drinking water. If you have any questions regarding this Water Quality Report, contact Pablo Ramudo, Water Quality Supervisor, (415) 761-8929 or (800) 464-6693.



This report is available on our website: www.nmwd.com

North Marin Water District's Stafford Lake Water Treatment Plant produces about 25% of the water needed for Novato. This facility is designed to produce water which meets or exceeds strict state and federal standards for water quality. The water treatment process starts with chlorine dioxide and polymers prior to filtration through layers of anthracite and garnet sand. The water then passes through granular activated charcoal to remove any remaining impurities before adjusting the pH to 8.3 for corrosion control and the addition of a small amount of chlorine for disinfection.

Most of Novato's water supply is purchased as treated water from Sonoma County Water Agency (SCWA).

The SCWA water supply is collected from gravel beds 80 feet below and adjacent to the Russian River. The quality of this naturally filtered water is excellent, making additional treatment unnecessary. Water from additional SCWA wells in the Santa Rosa plain can be blended with the Russian River well water to augment water supply. Before delivering the water to Novato, SCWA adds small amounts of chlorine and sodium hydroxide to ensure purity and to adjust the pH to 8.3.

The Stafford Lake water supply blends with the SCWA water supply in the Novato water distribution system. The percentage from each source can vary by day and by season.

Este informe contiene información muy importante sobre su agua potable. Tradúzcalo o hable con alguien que lo entienda bien. Para más información, llame al (415) 761-8929.

ONSTITUENT	Primary Drinking Water Standard (PDWS)						WATER AGENCY		TREATMENT PLANT	
	UNITS	PHG / [MRDLG] (MCLG)	MCL / [MRDL] (PDWS)	TYP	PICAL SOURCE	Average	Rang	ge Av	erage	Range
Fluoride	mg/L	1.0	2.0	Erosion	of natural deposits	ND	ND)	0.1	ND -0.12
Nitrate (as N)	mg/L	10	10	Soil runoff from septic sy	n fertilizers, leaching from ystems and sewage	ND	ND		ND	ND -0.52
Radioactivity Gross Alpha	pCi/l	0	15	Erosion	of natural deposits	ND (1)	ND (1) N	D (2)	ND (2)
				·			DISTRIBU	TION SYSTE	M WATER	R
Chlorine, Free	mg/L	[4.0]	[4.0] Drinking water disinfectant added for treatment			Average = 0.63 Range = 0.05 - 2.90				
Total Coliform Bacteria	% of samples positive	(0)	>5% of monthly Naturally present in samples the environment positive			March 2019 1% of samples positive (1 sample), September 2019 1% of samples positive (1 sample) 1019 samples collected in 2019				
Total rihalomethanes (3)	μg/L	n/a	80	By-prod	uct of drinking water disinfection	Highest Location Running Annual Average = 58.5 Range = 3.5 - 51.0				
Total Haloacetic Acids (3)	µg/L	n/a	60	By-prod	uct of drinking water disinfection	Highe	est Location Ra	Running Annu ange = ND - 17.	al Average .1	e = 21.0
Copper (4)	µg/L	170	(AL 1300)	Internal co plu	orrosion of household Imbing systems	30 sar 9	mples collect 90th percenti	ted, none abov ile = 107, Rang	ve the activ ge = ND - 1	on level 120
				30 samples collected, none above the action level 90th Percentile = ND, Range = ND - 12						
Lead (4) ABLE 2 Constitu	μg/L uents With Aest	2 Shetic Conce	(AL 15)	Internal c	Imbing systems	SONOMA	90th Percent	tile = ND, Rang	TAFFORI	12 D WATER
Lead (4) ABLE 2 Constitu Second	μg/L Jents With Aest ary Drinking Wa	2 hetic Conce ater Standar	(AL 15) rns and/or a d		Imbing systems	SONOMA WATER A	90th Percent COUNTY AGENCY Range	tile = ND, Rang	TAFFORI REAMEN	12 D WATER IT PLANT Range
Lead (4) ABLE 2 Constitu Seconda CONSTITUENT Color	μg/L uents With Aest ary Drinking Wa UNITS PCU	2 thetic Conce ater Standar SMCL 15	(AL 15)	TYPICAL SOU	RCE nic materials	SONOMA WATER A Average ND	90th Percent COUNTY AGENCY Range ND-4	tile = ND, Rang S TI e Ave	TAFFORI REAMEN rage	12 D WATER IT PLANT Range ND
Lead (4) ABLE 2 Constitution CONSTITUENT Color Odor	μg/L uents With Aest ary Drinking Wa UNITS PCU TON	2 thetic Conce ater Standar SMCL 15 3	(AL 15) rns and/or a d Nat	TYPICAL SOUI turally-occurring orga	RCE nic materials	SONOMA WATER A Average ND ND	Oth Percent AGENCY Range ND-4 ND	tile = ND, Rang S TI e Ave N	TAFFORI REAMEN rage ID	12 D WATER IT PLANT Range ND ND
Lead (4) ABLE 2 Constitu Second CONSTITUENT Color Odor Chloride	μg/L uents With Aest ary Drinking Wa UNITS PCU TON mg/L	2 thetic Conce ater Standar SMCL 15 3 500	(AL 15)	TYPICAL SOU turally-occurring orga turally-occurring orga	RCE nic materials unic materials ural deposits	SONOMA WATER A Average ND ND 5	Oth Percent COUNTY AGENCY Range ND-4 ND 4.7 – 5.	tile = ND, Rang	TAFFORI REAMEN rage ID ID	12 D WATER IT PLANT Range ND ND 38 – 65
Lead (4) ABLE 2 Constitu Second CONSTITUENT Color Odor Odor Chloride Sulfate	μg/L uents With Aestary Drinking Wa UNITS PCU TON mg/L mg/L	2 thetic Conce ater Standar SMCL 15 3 500 500	(AL 15) rns and/or a d Nat Nat Ru Leaching	TYPICAL SOU turally-occurring orga turally-occurring orga noff / leaching of natu of natural deposits, tr	RCE nic materials ural deposits eatment chemicals	SONOMA WATER A Average ND ND 5 12.5	90th Percent AGENCY Range ND-4 ND 4.7 – 5. 12 – 14	tile = ND, Rang S TI e Ave N 6 5 4 7	TAFFORI REAMEN rage ID ID 51 51	12 D WATER IT PLANT Range ND ND 38 - 65 6.8 - 8.5
Lead (4) ABLE 2 Constitu Second CONSTITUENT Color Color Chloride Sulfate Turbidity	μg/L Juents With Aestary Drinking Wathow OUNITS PCU TON mg/L mg/L NTU	2 thetic Conce ater Standar SMCL 15 3 500 500 5	(AL 15)	TYPICAL SOU turally-occurring orga turally-occurring orga noff / leaching of natu of natural deposits, tr Soil runoff	RCE nic materials unic materials ural deposits eatment chemicals	SONOMA WATER A Average ND ND 5 12.5 0.04	90th Percent COUNTY AGENCY Range ND-4 ND 4.7 – 5.1 12 – 14 0.02 – 2	tile = ND, Rang S TI e Ave N 6 5 4 7 .0 0.	TAFFORI REAMEN rage ID ID 51 '.8 .07	12 D WATER IT PLANT Range ND ND 38 - 65 6.8 - 8.5 0.04 - 0.08
Lead (4) ABLE 2 Constitu Second CONSTITUENT Color Color Chloride Sulfate Turbidity tal Dissolved Solids	μg/L Jumps Jumps Jumps Jumps Jumps PCU TON mg/L MTU mg/L	2 thetic Conce ater Standar SMCL 15 3 500 500 500 5 1000	(AL 15)	TYPICAL SOU turally-occurring orga turally-occurring orga inoff / leaching of natu of natural deposits, tr Soil runoff inoff / leaching of natu	RCE nic materials ural deposits ural deposits	SONOMA SONOMA WATER Average ND Sold 12.5 0.04 145	90th Percent AGENCY Range ND-4 ND 4.7 – 5. 12 – 14 0.02 – 2 140 – 16	tile = ND, Rang S TI e Ave N 6 5 4 7 .0 0. 50 11	TAFFORI REAMEN rage ID 51 2.8 .007 70	12 D WATER IT PLANT Range ND ND 38 – 65 6.8 – 8.5 0.04 – 0.08 170 – 180
Lead (4) ABLE 2 Constitut Second CONSTITUENT Color Color Color Chloride Sulfate Turbidity tal Dissolved Solids Sodium	μg/L Jents With Aestary Drinking Water UNITS PCU TON mg/L mg/L mg/L mg/L mg/L mg/L	2 thetic Conce ater Standar SMCL 15 3 500 500 500 500 1000 n/a	(AL 15)	TYPICAL SOU turally-occurring orga turally-occurring orga noff / leaching of natu of natural deposits, tr Soil runoff unoff / leaching of natu	RCE nic materials ural deposits tment chemicals	SONOMA SONOMA WATER A Average ND 5 12.5 0.04 145 8.5	90th Percent AGENCY Range ND-4 ND 4.7 – 5. 12 – 14 0.02 – 2 140 – 16 7.8 - 9.	tile = ND, Rang S TI Ave Ave N 6 5 4 7 .0 0 1 3 2	TAFFORI REAMEN rage ID ID S1 28	12 D WATER IT PLANT Range ND ND 38 – 65 6.8 – 8.5 0.04 – 0.08 170 – 180 24 – 31
Lead (4) ABLE 2 Constitue Color Col	μg/L Jumple Jumple Jumple Jumple PCU TON mg/L	2 thetic Conce ater Standar SMCL 15 3 500 500 500 500 0 1000 n/a n/a	(AL 15)	TYPICAL SOU turally-occurring orga turally-occurring orga inoff / leaching of natu of natural deposits, tr Soil runoff inoff / leaching of natu lly-occurring and trea Leaching of natural deposits	Imbing systems RCE nic materials unic materials ural deposits eatment chemicals ural deposits tment chemicals deposits	SONOMA SONOMA WATER Average ND SONOMA SONOMA	90th Percent COUNTY AGENCY Range ND-4 ND 4.7 – 5.1 12 – 14 0.02 – 2 140 – 16 7.8 - 9.3 110 – 12	tile = ND, Rang S F Ave Ave N 6 5 4 7 .0 0 0 1 3 2 20 8	TAFFORI REAMEN rage ID ID ID S1 28 35	12 D WATER IT PLANT Range ND ND 38 – 65 6.8 – 8.5 0.04 – 0.08 170 – 180 24 – 31 69 – 96
Lead (4) ABLE 2 Constitute Color Co	μg/L μg/L <	2 thetic Conce ater Standar SMCL 15 3 500 500 500 500 0 1000 n/a n/a n/a n/a	(AL 15)	TYPICAL SOU turally-occurring orga turally-occurring orga turally-occurring orga tooff / leaching of natu of natural deposits, tr Soil runoff unoff / leaching of natu lly-occurring and trea Leaching of natural of See "Radon in Air," ba	RCE nic materials ural deposits tment chemicals deposits tment chemicals	SONOMA SONOMA WATER Average ND Sonom ND Sonom ND Sonom ND Sonom Sonom ND Sonom Sonom ND Sonom Sonom <thsonom< th=""> <thsonom< th=""></thsonom<></thsonom<>	90th Percent AGENCY Range ND-4 ND 4.7 – 5. 12 – 14 0.02 – 2 140 – 16 7.8 - 9.3 110 – 12 45 – 15	tile = ND, Rang S TI e Ave N 6 5 4 7 .0 0. 50 11 3 2 20 8 0 n.	TAFFORI REAMEN rage ID ID ID S1 28 35 /a	12 D WATER IT PLANT Range ND ND 38 – 65 6.8 – 8.5 0.04 – 0.08 170 – 180 24 – 31 69 – 96 n/a
Lead (4) ABLE 2 Constitu Second CONSTITUENT Color Color Color Chloride Sulfate Turbidity tal Dissolved Solids Sodium Hardness (4) Radon ecific Conductance	μg/L	2 thetic Conce ater Standar SMCL 15 3 500 500 500 500 0 1000 0 1000 0 1000 0 1000 0 1000 0 1600	(AL 15)	TYPICAL SOU TYPICAL SOU turally-occurring orga turally-occurring orga inoff / leaching of natu of natural deposits, tr Soil runoff inoff / leaching of natu lly-occurring and trea Leaching of natural of See "Radon in Air," ba ubstances that form io	RCE nic materials unic materials ural deposits eatment chemicals tment chemicals deposits tack page ons in water	SONOMA SONOMA WATER Average ND SONOMA Average Ind Sonom Sonom Ind Sonom Ind Sonom Ind <	90th Percent COUNTY AGENCY Range ND-4 ND 4.7 – 5.4 12 – 14 0.02 – 2 140 – 16 7.8 - 9.3 110 – 12 45 – 15 210 – 25	tile = ND, Rang S Ave Ave Ave A A A A A A A A	TAFFORI REAMEN rage ID ID ID S1 28 35 /a 20	12 D WATER IT PLANT Range ND ND 38 – 65 6.8 – 8.5 0.04 – 0.08 170 – 180 24 – 31 69 – 96 n/a 260 – 350

LEGEND

- (Public Health Goal): The level of a contaminant in drinking water below there is no known or expected risk to health. PHGs are set by the California onmental Protection Agency.
- **G** (Maximum Contaminant Level Goal): The level of a contaminant in drinking below which there is no known or expected risk to health. MCLGs are set by .S. Environmental Protection Agency (EPA).
- (Maximum Contaminant Level): The highest level of a contaminant that is ed in drinking water. Primary MCLs are set as close to the PHGs (or MCLGs) as is omically and technologically feasible. Secondary MCLs (SMCL) are set to protect dor, taste, and appearance of drinking water. MCLs and SMCLs are set by the rnia and/or U.S. EPA.
- **5 (Primary Drinking Water Standard):** MCLs and MRDLs, for contaminants affect health along with their monitoring and reporting requirements, and treatment requirements.
- **Action Level):** The concentration of a contaminant that, if exceeded, triggers nent or other requirements that a water system must follow.
- **reatment Technique):** A required process intended to reduce the level of a minant in drinking water.
- (Nephelometric Turbidity Units): A measure of suspended material in water.
- Percentile: Compliance based on highest value after eliminating the highest
- L (Maximum residual disinfectant level): The level of a disinfectant added for treatment that may not be exceeded at the consumer's tap.
- **LG (Maximum residual disinfectant level goal):** The level of a disinfectant d for water treatment below which there is no known or exposed risk to health. .Gs are set by the U.S. EPA.
- lotification Level): The notification level for some unregulated contaminants.
- = milligrams per liter (parts per million) -equivalent to 4 drops of water in the average sized bathtub.
- micrograms per liter (parts per billion) -equivalent to 50 drops in an olympic size swimming pool
- **s/cm** = micromhos per centimeter
- Not Detected
- Not Applicable
- platinum cobalt units
- = picocuries per liter

pliance based on a four-quarter running average at each distribution system monitoring location

age hardness shown in mg/L equates to 5.0 - 6.4 grains per gallon.

Concerning Lead and Drinking Water

If present, elevated levels of lead can cause serious health problems, especially for pregnant women and young children. There is no lead in drinking water produced by NMWD and there are no district owned lead service lines within our system, however lead can leach into drinking water from materials and components associated with customers' service lines and home plumbing. NMWD is responsible for providing high quality drinking water to your meter, but cannot control the variety of materials used in home plumbing components. When water in your household plumbing has been sitting for several hours, you can minimize the potential for lead exposure by running your tap water for 30 seconds to 2 minutes before using water for drinking or cooking. If you are concerned about lead in your water, you may wish to have your water tested. Information on lead in drinking water, testing methods, and steps you can take to minimize exposure is available from the Safe Drinking Water Hotline or at www.epa.gov/safewater/lead.

A Message From the United States Environmental Protection Agency

The sources of drinking water (both tap water and bottled water) include rivers, lakes, streams, ponds, reservoirs, springs, and wells. As water travels over the surface of the land or through the ground, it dissolves naturally occurring minerals and, in some cases, radio-

human activity. Contaminants that may be present in source water include:

active materials, and can pick up substances

resulting from the presence of animals or from

- Microbial Contaminants, such as viruses and bacteria, that may come from sewage treatment plants, septic systems, agricultural livestock operations, and wildlife.
- Inorganic Contaminants, such as salts and metals, that can be naturally occurring or result from urban stormwater runoff, industrial or domestic wastewater discharges, oil and gas production, mining or farming.
- Pesticides and Herbicides, that may come from a variety of sources such as agriculture, urban stormwater runoff, and residential uses.
- <u>Organic Chemical Contaminants</u>, including synthetic and volatile organic chemicals, that are by-products of industrial processes and petroleum production, and can also come from gas stations, urban stormwater runoff, agricultural applications and septic systems.
- <u>Radioactive Contaminants</u>, that can be naturally-occurring or be the result of oil and gas production and mining activities.

In order to ensure that tap water is safe to drink, the U.S. Environmental Protection Agency (USEPA) and the California Department of Public Health (CDPH) prescribe regulations that limit the amount of certain contaminants in water provided by public water systems. DHS regulations also establish limits for contaminants in bottled water that provide the same protection for public health.

Drinking water, including bottled water, may reasonably be expected to contain at least small amounts of some contaminants. The presence of contaminants does not necessarily indicate that water poses a health risk. More information about contaminants and potential health effects can be obtained by calling the USEPA's Safe Drinking Water Hotline (1-800- 426-4791).

Some people may be more vulnerable to contaminants in drinking water than the general population. Immuno-compromised persons such as persons with cancer undergoing chemotherapy, persons who have undergone organ transplants, people with HIV/AIDS or other immune system disorders, some elderly, and infants can be particularly at risk from infections. These people should seek advice about drinking water from their health care providers. USEPA/Centers for Disease Control (CDC) guidelines on appropriate means to lessen the risk of infection by Cryptosporidium and other microbial contaminants are available from the Safe Drinking Water Hotline (1-800-426-4791).

Drinking Water Source Assessment for SCWA Groundwater Supply

In January 2001, a Drinking Water Source Assessment for all of the SCWA's water sources was conducted to identify if any potential sources of contamination exist.

The SCWA source water is extracted from groundwater via 6 Rainey Collector Wells and 7 conventional wells located at Wohler and Mirabel, and three wells in the Santa Rosa Plain. The aquifer is recharged by subsurface flows and Russian River water filtering down through the gravel riverbed.

Most of the SCWA water supply comes from wells at Wohler and Mirabel adjacent to the Russian River. These sources are considered to be most vulnerable from wastewater treatment and gravel mining in the area. However, no contaminants associates with these activities were detected in the drinking water.

The SCWA also operates three groundwater wells on the Santa Rosa Plain near Occidental Road, Todd Road and Sebastopol Road. These sources are considered to be most vulnerable from animal feeding operations. However, no contaminants associated with this activity were detected in the drinking water.

A copy of the complete assessment may be reviewed at the California Department of Public Health, Drinking Water Field Operations Branch, 50 D Street, Suite 200, Santa Rosa, CA 95404. You may request a summary of this assessment be sent to you by contacting the Office Representative at 707-576-2145 (voice) or 707-576-2722 (fax).

Cryptosporidium & Giardia

Monitoring performed by NMWD on untreated water in Stafford Lake has intermittently shown the presence of cryptosporidium, a microbial pathogen found in surface waters throughout the U.S. NMWD's filtration is designed and operated to remove cryptosporidium, but 100% removal cannot be guaranteed. Should you be concerned? Healthy individuals should not be concerned. However, immuno-compromised people are at greater risk. We suggest immuno-compromised individuals consult their physician regarding appropriate precautions.

Radon In Air

Radon is a radioactive gas that can move from decomposed granite soils into a home through cracks and holes in the foundation. Radon can also get into indoor air when running tap water for showering and other household activities. In most cases, radon from tap water is a small source of radon in air. Radon is a known human carcinogen. It can lead to lung cancer. Drinking water containing radon may also cause increased risk of stomach cancer. The SCWA water was tested for Radon and showed an average of 94 and a range of 45 – 150 pCi/L (picocuries per liter). There is no federal regulation for radon levels in drinking water. Exposure over a long period of time to air transmitting radon may cause adverse health effects. If you are concerned about radon in your home, test the air in your home! Testing is inexpensive and easy. For additional information, call your state radon program or call EPA's Radon Hotline (800-SOS-RADON).

Notice To Kidney Dialysis Patients

Chlorine dioxide is used as a pre-oxidant in water produced from Stafford Water Treatment Plant. Customers undergoing kidney dialysis treatment are advised to use sufficient pre-treatment to ensure chlorine dioxide does not pose a threat to the dialysis process.

Drinking Water Source Water Assessment For Stafford Lake

An assessment of watershed activities, which may affect the Stafford Lake source of supply, was performed in 2002 as required by the U.S. Environmental Protection Agency. The watershed activities identified with the highest potential for contamination of Stafford Lake are animal feeding/ waste disposal at the existing stable and dairy operations on the watershed. These activities increase the potential to introduce microbial contaminants and nutrients to Stafford Lake. NMWD actively works with the stable and dairy owners to control their operations and reduce potential contaminants. The Stafford Lake source water is routinely monitored by NMWD to insure the controls are effective.

A copy of the complete assessment is on file at the North Marin Water District office at 999 Rush Creek Place, Novato.