

2018 Water Quality Report to

Water Facilities Authority Member Agencies

Parameter	Units	State or Federal MCL [MRDL]	PHG (MCLG) [MRDLG]	State DLR	Range	Average	Major Sources in Drinking Water
CLARITY							
Combined Filter Effluent	NTU	TT=1 NTU	NA	NA		lighest	
Turbidity MICROBIOLOGICAL	%	TT (a)			% ≤ 0.3	100%	Soil runoff
Total Coliform		1		[1	[
Bacteria	%	5.0 (b)	(0)	NA	0	0	Naturally present in the environment
E. coli	(c)	(c)	(0)	NA	0	0	Human and animal fecal waste
SYNTHETIC ORGANIC CO	ONTAMINATS	i					
100511	a a b	0.005				ND	Discharge from industrial and agricultural chemical
1,2,3-Trichloropropane	ppb	0.005	0.0007	0.005	ND	ND	factories; leaching from hazardous waste sites.
INORGANIC CHEMICALS	1	1					Desidue from water treatment process
Aluminum (d)	ppb	1000	600	50	ND - 97	38	Residue from water treatment process; Erosion of natural deposits
	11.				112 01		Natural deposits erosion, glass and
Arsenic	ppb	10	0.004	2	ND	ND	electronics production wastes
Fluoride (naturally-occurring)	ppm	2	1	0.1	ND - 0.41	0.15	Erosion of natural deposits; water additive that promotes strong teeth
(naturally-occurring)	ppin	2	1	0.1	ND - 0.41	0.15	Runoff & leaching from fertilizer use;
Nitrate (as N) (e)	ppm	10	10	0.4	ND - 2.1	0.8	sewage; erosion of natural deposits
				<u> </u>		ND	Runoff & leaching from fertilizer use;
Nitrite (as N)	ppm	1	1	0.4	ND	ND	sewage; erosion of natural deposits Runoff & leaching from fertilizer use;
Nitrate and Nitrite (as N)	ppm	10	10	0.4	ND - 2.1	0.8	sewage; erosion of natural deposits
RADIOLOGICALS							• •
Gross Alpha	2 1/						
Particle Activity	pCi/L	15	(0)	3	ND	ND	Erosion of natural deposits
DISINFECTION BY-PROD	UCTS, DISINF	ECTANT RES	SIDUALS, AND	DISINFECTI	ON BY-PROD	UCTS PRECU	
Total Trihalomethanes (f)	ppb	80	NA	1	29 - 60	54	By-product of drinking water chlorination
Haloacetic Acids (five)	nnh	60	NIA	4	7 10	11	By-product of drinking water
(HAA5) (f) Total Chlorine Residual	ppb	60	NA	1	7 - 13		chlorination Drinking water disinfectant added
(Distribution System-wide)	ppm	[4.0]	[4.0]	NA	0.54 - 2.10	1.31	for treatment
DBP Precursors Control							
Total Organic Carbon (TOC)	ppm	TT	NA	0.30	TT	TT	Various natural and man-made sources
SECONDARY STANDARD	S-Aestnetic a	standards		-		-	Residue from water treatment process;
Aluminum (d)	ppb	200	600	50	ND - 97	38	Erosion of natural deposits
							Runoff/leaching from natural deposits;
Chloride	ppm	500	NA	NA	3.3 - 89.0	48.7	seawater influence
Color	Units	15	NA	NA	ND	ND	Naturally occurring organic materials
MBAS	ppb	500	NA	NA	ND	ND	Natural deposits erosion: wood preservatives leaching
Odor Threshold	TON	3	NA	1	ND - 2.0	1.3	Naturally occurring organic materials
Specific Conductance	µS/cm	1600	NA	NA	380 - 500	442	Substances that form ions when in water; seawater influence
	p0/011	1000		11/4	300 - 300	-	Runoff/leaching from natural deposits;
Sulfate	ppm	500	NA	0.5	25 - 49	35	industrial wastes
Total Dissolved Solids	ppm	1000	NA	NA	230 - 290	262	Runoff/leaching from natural deposits; seawater influence
Turbidity (a)	NTU	5	NA	0.1	0.05 - 0.30	0.09	Soil runoff
Iron	ррb	300	NA	100	ND	ND	Leaching from natural deposits; industrial wastes



2018 Water Quality Report to

Water Facilities Authority Member Agencies

Parameter	Units	Federal MCL [MRDL]	PHG (MCLG) [MRDLG]	State DLR	Range	Average	Major Sources in Drinking Water
OTHER PARAMETERS							
Alkalinity	ppm	NA	NA	NA	58 - 180	103	
Bicarbonate	ppm	NA	NA	NA	70 - 220	126	
Boron	ppb	NL=1000	NA	100	ND - 160	68	Runoff/leaching from natural deposits; industrial wastes
Calcium	ppm	NA	NA	NA	18 - 60	32	
Corrosivity (g) as (Aggressiveness Index)	AI	NA	NA	NA	12.0 - 12.1	12.0	Elemental balance in water; affected by temperature, other factors
Corrosivity (h) as (Saturation Index Index)	SI	NA	NA	NA	0.29 - 0.43	0.36	Elemental balance in water; affected by temperature, other factors
Hardness (CaCO₃) (Total Hardness)	ppm	NA	NA	NA	86 - 190	124	Leaching from natural deposits
Magnesium	ppm	NA	NA	NA	7.8 - 12.0	10.2	
рН	pH Units	NA	NA	NA	8.07 - 8.80	8.47	
Potassium	ppm	NA	NA	NA	1.9 - 2.8	2.4	
Sodium	ppm	NA	NA	NA	11 - 58	39	Runoff/leaching from natural deposits; seawater influence
тос	ppm	тт	NA	0.3	1.8 - 2.8	2.3	Various natural and man-made sources
Vanadium	ppb	NL=50	NA	3	ND - 4.9	3.4	Naturally-occurring; industrial waste discharge

ABBREVIATIONS

DBP	Disinfection by-products	NTU	Nephelometric Turbidity Units
DLR	Detection Limits for Purpose of Reporting	pCi/L	PicoCouries per liter
MCL	Maximum Contaminate Level	PHG	Public Health Goal
MCLG	Maximum Contaminant Level Goal	ppb	Parts Per Billion
MRDL	Maximum Residual Disinfectant Level	ppm	Parts Per Million
MRDLG	Maximum Residual Disinfectant Level Goal	TOC	Total Organic Carbon
NA	Not Applicable	TON	Threshold Odor Number
ND	Monitored for but not detected	TT	Treatment Techniques
NL	Notification Level	μS/cm	MicroSiemen per centimeter

FOOTNOTES

(a)	As a Primary Standard, the turbidity levels of the filtered water were less than or equal to 0.3 NTU in 95% of
	the online measurements taken each month and did not exceed 1 NTU for more than one hour. Turbidity, a
	measure of cloudiness of the water, is an indicator of the treatment performance.
	The turbidity levels for distribution grab samples were in compliance with the Secondary Standard.
(b)	Total coliform Rule: No more than 5% of the monthly samples may be total coliform-positive. Standards and
	results are based on distribution system monthly sampling averages. In 2018, 562 samples were analyzed
	and zero (0) samples were positive for total coliforms. The MCL was not violated.
(c)	E. Coli MCL: The occurrence of two (2) consecutive total coliform positive samples, one of
	which contains E. Coli constitutes an acute MCL violation. The MCL was not violated in 2018.
(d)	Aluminum has both primary and secondary standards.
(e)	Nitrate is reported either as NO ₃ or as nitrogen N. To convert data from N to NO ₃ , multiply by 4.43
(f)	WFA was in compliance with all provisions of Stage 2 Disinfectant/Disinfection By-Products Rules
	(D/DBPR). Compliance was based on the highest Locational Running Annual Average (LRAA) of all data collected
	at distribution system-wide monitoring locations. The averages reported for THM's and HAA5 is the highest LRAA.
(g)	AI ≥ 12.0 =Non-aggressive water, AI (10.0-11.9) =Moderately aggressive water, AI ≤ 10.0 =Highly aggressive water
(h)	Positive SI index=Non-corrosive; tendency to precipitate and/or deposit scale on pipes. Negative SI index=corrosive;
	tendency to dissolve calcium carbonate.