

## 2024 Water Quality Report to Water Facilities Authority Member Agencies

		State or					
Parameter	Units	Federal MCL [MRDL]	PHG (MCLG) [MRDLG]	State DLR	Range	Average	Major Sources in Drinking Water
CLARITY	. ITI I				0.44.1	l'ala a a t	
Combined Filter Effluent Turbidity	NTU %	TT=1 NTU TT (a)	NA	NA		lighest 99.4%	Soil runoff
MICROBIOLOGICAL							
Total Coliform							
Bacteria	%	5.0 (b)	(0)	NA	0.0 - 2.0	0.2	Naturally present in the environment
E. coli	(c)	(c)	(0)	NA	ND	ND	Human and animal fecal waste
SYNTHETIC ORGANIC CO	MPOUNDS (	d)					
Diguet	nnh	20	6	4	10	18	Runoff from herbicide used for terrestrial
Diquat INORGANIC CHEMICALS	ppb	20	6	4	18	10	and aquatic weeds
INCKCANIO CHEMICAEC		I					Residue from water treatment process;
Aluminum (e)	ppb	1000	600	50	ND - 93	41	Erosion of natural deposits
Araonia	ppb	10	0.004	2	ND	ND	Natural deposits erosion, glass and
Arsenic Fluoride	ppu	10	0.004	2	ND	ND	electronics production wastes  Erosion of natural deposits; water
(naturally-occurring)	ppm	2	1	0.1	ND - 0.39	0.10	additive that promotes strong teeth
Nitrate (as N) (f)	ppm	10	10	0.4	ND 16	0.7	Runoff & leaching from fertilizer use; sewage; erosion of natural deposits
Militale (as N) (I)	ррпп	10	10	0.4	ND - 1.6	0.7	Runoff & leaching from fertilizer use;
Nitrite (as N)	ppm	1	1	0.4	ND	ND	sewage; erosion of natural deposits
Nitrata and Nitrita (as NI)	ppm	10	10	0.4	ND 16	0.7	Runoff & leaching from fertilizer use;
Nitrate and Nitrite (as N)  RADIOLOGICALS	рріп	10	10	0.4	ND - 1.6	0.1	sewage; erosion of natural deposits
Gross Alpha		I					
Particle Activity	pCi/L	15	(0)	3	-0.07 - 2.66	1.30	Erosion of natural deposits
DISINFECTION BY-PRODU	JCTS, DISINF	ECTANT RES	IDUALS, AND	DISINFECTIO	N BY-PRODU	ICTS PRECUI	
Total Trihalomethanes (g)	ppb	80	NA	1	28 - 76	56	By-product of drinking water chlorination
Haloacetic Acids (five)	ррь	80	INA	1	28 - 70	- 00	By-product of drinking water
(HAA5) (f)	ppb	60	NA	1	3 - 18	14	chlorination
Total Chlorine Residual (Distribution System-wide)	ppm	[4.0]	[4.0]	NA	1.11 - 1.30	1.19	Drinking water disinfectant added for treatment
DBP Precursors Control	РРП	[4.0]	[4.0]	INA	1.11 - 1.50	1.10	ioi treatment
Total Organic Carbon (TOC)	ppm	TT	NA	0.30	TT	TT	Various natural and man-made sources
SECONDARY STANDARDS-Aesthetic Standards							
Aluminum (e)	ppb	200	600	50	ND - 93	41	Residue from water treatment process; Erosion of natural deposits
riammam (o)	FF*	200	000	00	112 00		Runoff/leaching from natural deposits;
Chloride	ppm	500	NA	NA	2.8 - 64.0	37.0	seawater influence
Color	Units	15	NA	NA	ND	ND	Naturally occurring organic materials
Manganese	ppb	50	NL=500	20	ND	ND	Leaching from natural deposits
Wanganese		50	142-300	20	ND		Natural deposits erosion: wood
MBAS	ppb	500	NA	NA	ND	ND	preservatives leaching
Odor Threshold	TON	3	NA	1	ND - 2.0	0.5	Naturally occurring organic materials
Specific Conductance	μS/cm	1600	NA	NA	290 - 450	395	Substances that form ions when in water; seawater influence
	•	500				34	Runoff/leaching from natural deposits; industrial wastes
Sulfate	ppm		NA	0.5	21 - 51		Runoff/leaching from natural deposits;
Total Dissolved Solids	ppm	1000	NA	NA	170 - 260	228	seawater influence
Turbidity (a)	NTU	5	NA	0.1	0.1 - 2.0	0.6	Soil runoff
Iron	ppb	300	NA	100	ND	ND	Leaching from natural deposits; industrial wastes



## 2024 Water Quality Report to Water Facilities Authority Member Agencies

Parameter	Units	State or Federal MCL [MRDL]	PHG (MCLG) [MRDLG]	State DLR	Range	Average	Major Sources in Drinking Water
OTHER PARAMETERS							
Alkalinity	ppm	NA	NA	NA	68 - 180	112	
Bicarbonate	ppm	NA	NA	NA	83 - 220	135	
Calcium	ppm	NA	NA	NA	14.8 - 60.0	32.6	
Hardness (CaCO₃) (Total Hardness)	ppm	NA	NA	NA	69.9 - 190.0	119.1	Leaching from natural deposits
Magnesium	ppm	NA	NA	NA	7.99 - 10.90	9.40	
рН	pH Units	NA	NA	NA	7.12 - 8.34	7.70	
Potassium	ppm	NA	NA	NA	1.8 - 3.2	2.4	
Sodium	ppm	NA	NA	NA	9.8 - 46.0	28.6	Runoff/leaching from natural deposits; seawater influence
TOC	ppm	TT	NA	0.3	1.6 - 2.8	2.3	Various natural and man-made sources
Vanadium	ppb	NL=50	NA	3	1.9 - 3.9	3.0	Naturally-occurring; industrial waste discharge

## **ABBREVIATIONS**

DBP	Disinfection by-products	NTU	Nephelometric Turbidity Units
DLR	Detection Limits for Purpose of Reporting	pCi/L	PicoCouries per liter
MCL	Maximum Contaminate Level	PHG	Public Health Goal
MCLG	Maximum Contaminant Level Goal	ppb	Parts Per Billion
MRDL	Maximum Residual Disinfectant Level	ppm	Parts Per Million
MRDLG	Maximum Residual Disinfectant Level Goal	TOC	Total Organic Carbon
NA	Not Applicable	TON	Threshold Odor Number
ND	Monitored for but not detected	TT	Treatment Techniques
NL	Notification Level	μS/cm	MicroSiemen per centimeter

## **FOOTNOTES**

- (a) As a Primary Standard, the turbidity levels of the combined filtered water were less than or equal to 0.3 NTU in 95% of the online measurements taken each month and did not exceed 1 NTU for more than one hour. Turbidity, a measure of cloudiness of the water, is an indicator of the treatment performance. Turbidity was in compliance with the TT primary drinking water standard and the secondary drinking water standard of less than 5 NTU.
- (b) Total coliform Rule: No more than 5% of the monthly samples may be total coliform-positive. Standards and results are based on distribution system monthly sampling averages. In 2024, 569 samples were analyzed and One (1) sample was positive for total coliforms. The MCL was not violated.
- (c) E. Coli MCL: The occurrence of two (2) consecutive total coliform positive samples, one of which contains E. Coli constitutes an acute MCL violation. The MCL was not violated in 2024.
- (d) Monitoring frequency is once every 3 years. Last monitoring results are from 2023.
- (e) Aluminum has both primary and secondary standards.
- (f) Nitrate is reported either as NO<sub>3</sub> or as nitrogen N. To convert data from N to NO<sub>3</sub>, multiply by 4.43
- (g) WFA was in compliance with all provisions of Stage 2 Disinfectant/Disinfection By-Products Rules
  - (D/DBPR).Compliance was based on the highest Locational Running Annual Average (LRAA) of all data collected at distribution system-wide monitoring locations. The averages reported for THM's and HAA5 is the highest LRAA.