The U.S. Environmental Protection Agency and the State Water Resources Control Board have regulations that limit the amount of certain contaminants allowed in water provided by public water systems to ensure that tap water is safe to drink. Drinking water, including bottled water, may reasonably be expected to contain at least small amounts of some contaminants. The presence of contaminants does not necessarily indicate that water poses a health risk. More information about contaminants and potential health effects can be obtained by calling the U.S. EPA's Safe Drinking Water Hotline at 800-426-4791.

Carlsbad MWD has sampled all required data including entry points in the distribution system for the fourth Unregulated Contaminant Monitoring Rule (UCMR 4) contaminants in 2020. The analytical results for UCMR 4 are stored in the National Contaminant Occurrence Database for drinking water, which can be found online at www.epa.gov/sdwa/national-contaminant-occurrence-database-ncod.

Water Conservation

Carlsbad encourages residents and businesses to continue making water conservation a way of life. With water being a precious and limited resource, Carlsbad is doing our part by making water conservation and the efficient use of water a major priority. Even the simplest changes to daily routines make a difference.

Do your part by following the water conservation tips below, and visit www.carlsbadca.gov/departments/utilities/water/conservation for programs, incentives, water rules, and more tips and resources.

Indoo

- · Take short showers or fill the bathtub halfway
- · Turn water off when brushing teeth or shaving
- · Wash only full loads of clothes
- Fix leaks (toilets, faucets, etc.)
- Install high-efficiency fixtures

Outdoor

- Install drip-irrigation
- Adjust sprinklers to reduce water lost from overspray onto impervious surfaces
- Water during cool parts of the day to reduce evaporation
- Install a smart irrigation controller
- Convert to a native landscape
- Repair broken sprinkler heads and/or irrigation lines (do not irrigate until repair is made)



How to contact us

This report covers testing for contaminants in 2018. For questions or concerns regarding the quality of Carlsbad's drinking water, contact the Carlsbad Municipal Water District at 760-438-2722 or email water@carlsbadca.gov.

To participate in decisions that affect drinking water in the Carlsbad Municipal Water District service area, please watch the Carlsbad Municipal Water District Board of Directors meeting agenda for drinking water items. Carlsbad Municipal Water District Board meetings are held in conjunction with the Carlsbad City Council on an as needed basis on Tuesday evenings. Agendas may be obtained at www.carlsbadca.gov or Carlsbad City Hall, 1200 Carlsbad Village

This report can be downloaded from www.carlsbadca.gov/water-quality-report.

Drive. Comments regarding drinking water are

Carlsbad Municipal Water District

always welcome.

5950 El Camino Real, Carlsbad, CA 92008 Hours: Monday through Friday, 8 a.m. to 5 p.m. 760-438-2722 • water@carlsbadca.gov

Additional sources for water quality information:

San Diego County Water Authority 858-522-6600 • www.sdcwa.org

Metropolitan Water District of Southern California

800-CALL-MWD (225-5693) www.mwdh2o.com

State Water Resources Control Board

Division of Drinking Water & Environmental Management 619-525-4159 • www.waterboardsca.gov

U.S. Environmental Protection Agency

Office of Ground Water & Drinking Water Safe Drinking Water Hotline 800-426-4791 www.epa.gov/safewater/hfacts.html



WATER QUALITY 2020 Report



Este informe contiene informacion muy importante sobre su agua potable. Traduzcalo o hable con alguien que lo entienda bien.

Water provided by the Carlsbad Municipal Water District meets all 2020 State and Federal drinking water standards. This report provides detailed water quality test results and explains where Carlsbad's water comes from.

Where Our Water Comes From

The Carlsbad Municipal Water District currently imports all of its drinking water. The water supply begins hundreds of miles away as snow melt or rainfall that flows into rivers. The two main water sources are the Colorado River, where the water is transported through the Colorado River Aqueduct, and Northern California, that brings the water through the California Aqueduct (also known as the State Water Project.)

Water from these sources is treated by the Metropolitan Water District of Southern California at its Lake Skinner Treatment Plant in Riverside County and by the San Diego County Water Authority. After rigorous treatment, the water travels through San Diego County Water Authority owned pipelines and is purchased and distributed by the Carlsbad Municipal Water District to its customers. The Claude "Bud" Lewis Carlsbad Desalination Plant delivers water to the San Diego County Water Authority, which blends the water with the region's imported water supply and delivers it to water agencies throughout San Diego County.

What's in your water before it's treated?

The sources of drinking water (both tap water and bottled water) include oceans, rivers, lakes, streams, ponds, springs and wells. As water travels over the surface of the land or through the ground, it dissolves naturally occurring minerals and, in some cases, pick up substances resulting from the presence of animals or from human activity.

Contaminants that may be present in source water include:

- Microbial contaminants, such as viruses and bacteria that can come from wastewater treatment plants, septic systems, agricultural livestock operations and wildlife.
- Inorganic contaminants, such as salts and metals, that can be naturally occurring or result from urban storm water runoff, industrial or domestic wastewater discharges, oil and gas production, mining or farming.

- Pesticides and herbicides, that can come from a variety of sources such as agriculture, urban stormwater runoff and residential uses.
- Organic chemical contaminants, including synthetic and volatile organic chemicals, that are byproducts of industrial processes and petroleum production, and can also come from gas stations, urban stormwater runoff,

Water has met all 2020 Federal and State Drinking Water Standards.

Carlsbad MWD

agricultural application and septic systems.

Radioactive contaminants, that can be naturally occurring or be the result of oil and gas production and mining activities.

Continued on page 4

California Aqueduct

2020 CARLSBAD **WATER QUALITY** ANALYSIS

Parameter	Units	State or Federal MCL [MRDL]	PHG (MCLG) [MRDL]	State DLR	Range Average	Skinner Plant Effulent	Twin Oaks Plant	CMWD System Samples	Carlsbad Desal Plant	Major Sources in Drinking Water
Percent State Project Water	%	NA	NA	NA	Range Average	0-100 62	NA NA	NA NA	NA NA	
				PRIMARY STA	ANDARDSMandatory He					
CLARITY Combined Filter	NTU	TT=1			Highest	0.10	0.01-0.02	NA	1.0	
Effluent Turbidity(a)	%	TT (a)	NA	NA	% ≤ 0.10	95%	95%	NA	99.7%	Soil runoff
MICROBIOLOGICAL	ı	l		ı	Range	0	ND	NA	ND	
Total Coliform Bacteria (b)	%	5.0	MCLG=0	NA	Average	0	ND	NA	ND	Naturally present in the environment
E. coli (c)	NA	TT	MCLG=0	NA	Positive sample	0	ND	NA	ND	Human and animal fecal waste
INORGANIC CHEMICALS										
	Ι.	40	0.004		Range	ND	2	NA	ND-	Natural deposits erosion, glass and electronics, production wastes
Arsenic	ppb	10	0.004	2	Average	ND	2	NA	0.42 0.42	retain deposits crossin, glass and decelorities, produced hases
2016 Copper Samples	ppm	AL = 1.3	0.3	0.05	No.>AL	NA	NA	ND	NA	Internal corrosion of household pipes natural deposits erosion
	pp	71.0	0.0	0.00	90%ile	NA	NA	ND	NA	
Fluoride (d) Control Range						0.5 - 0.9	0.6-1.2	NA	0.7-0.794	
	Optimal Fluoride Level					0.7	0.7	NA	0.750	
	ppm	2.0	1	0.1	Range	0.6-0.9	0.5-1.1	NA	NA	Erosion of natural deposits
Treatment-related Fluoride	ppiii	2.0		0.1	Average	0.7	0.7	NA	NA	water additive that promotes strong teeth
2016 Lead Samples (e)	nnh	15 ppb	0.2	5	No.>AL	NA	NA	0	NA	House pipes internal corrosion; erosion of natural deposits
2010 Ceau Gampies (e)	ppb	15 ррб	0.2	3	90%ile	NA	NA	0.0016	NA	nouse pages memar corroson, croson or natural deposits
AUG.					Range	ND	0.3-0.6	NA.	ND	Runoff and leaching from fertilizer use, septic tank and sewage; natural
Nitrate	ppm	10	10	0.4	Average	ND	0.5	NA NA	ND	deposits erosion
					RADIOLOGICALS					
Uranium	pCi/L	20	0.43	1	Range Average	ND-3	2.7-3.1	NA NA	ND ND	Erosion of natural deposits
		DISINF	ECTION BY-PRODU	ICTS, DISINFECTAN	T RESIDUALS, AND DISINFECT	ION BY-PRODUCT PRI	ECURSORS (o)			
Total Trihalomethanes (f) (TTHM)	ppb	80	NA	1.0	Range	14-38	14-80	14.0-32.0	ND	By-product of drinking water chlorination
,					Highest LRAA	19	39	22	ND	
(HAA5) Samples	ppb	60	NA	1.0	Range Highest LRAA	4.0-8.8 5.4	3.0-9.0 5.0	3.1-14.0 6.0	ND ND	By-product of drinking water chlorination
					Range					
Total Chlorine Residual	ppm	[4.0]	[4.0]	NA	Highest RAA	NA NA	0.4-3.7 3.2	1.99-2.66	2.67-3.42 3.14	Drinking water disinfectant added for treatment
	ppb	10	0.1	1.0	Range	ND-12	2.0-13	NA NA	NA	By-product of drinking water ozonation
Bromate (g) SECONDARY STANDARDS—Aesthetic Standards	ррь	10	0.1	1.0	Highest RAA	4.1	6.0	NA	NA	-,,
					Range	56-72	NA	NA	NA	
Chloride	ppm	500	NA	NA	Average	64	59	NA	NA	Runoff leaching from natural deposits seawater influence
Color	Units	15	NA	NA	Range	1	ND	NA	ND	Naturally-occurring organic materials
Odor Threshold				101	Average Range	1 3	ND NA	NA NA	ND ND	
Odor Infesticia	TON	3	NA	1	Average Range	3 455-571	1 NA	NA NA	ND 304.26-	Naturally-occurring organic materials
Specific Conductance	μS/cm	1600	NA	NA	Average	513	470	NA NA	694.09 430.70	Substances that form ions in water seawater influence
Sulfate	ppm	500	NA	0.5	Range	66-81	NA 50	NA NA	NA	Runoff leaching from natural deposits Industrial wastes
Total Dissolved Solids (TDS)					Average Range	74 259-321	56 NA	NA NA	NA 80-426	Runoff leaching from natural deposits seawater influence
Total Bissolited College (1997)	ppm	1000	NA	NA	Average OTHER PARAMETER	290 s	280	NA	232.7	
CHEMICAL										
Alkalinity	ppm	NA	NA	NA	Range Sample	62-78 70	NA 77	NA NA	48-88 59.7	
Boron	ppb	NL=1,000	NA	100	Range Average	110 110	NA 120	NA NA	.3395 .59	Runoff leaching from natural deposits, Industrial wastes
					Range	27-32	NA	NA	19.4-43.9	
Calcium	ppm	NA	NA	NA	Sample Range	30 23	26 180-360	NA NA	23.9 NA	
Chlorate	ppb	NL=800	NA	20	Range	23	244	NA NA	NA NA	By-product of drinking water chlorination Industrial processes
Chromium VI (h)	ppb	10	0.02	1	Range	ND	ND	NA	NA	Runoff leaching from natural deposits; discharge from industrial waste
			-		Average Range	ND 11.8-12.0	ND NA	NA NA	NA 11.30-12.01	factories
Corrosivity (i) (as Aggressiveness Index)	AI	NA	NA	NA	Average	11.9	12	NA	11.57	Elemental balance in water; affected by temperature, other factors
Corrosivity (j) (as Saturation Index)	SI	NA	NA	NA	Range Average	0.04-0.25 0.14	NA 0.55	NA NA	0.02-0.66	Elemental balance in water affected by temperature & other factors
(as Saturation Index) Hardness					Range	109-129	NA	NA	1183-7672	
Lead Sampling in (8) schools	ppm	NA	NA	NA	Sample No.>AL	119 NA	110 NA	NA ND-0.0057	6133 NA	
	ppm	AL=0.015	0.2	5	90%ile	NA	NA	0.0012	NA	Internal erosion of natural deposits.
Magnesium	ppm	NA	NA	NA	Range Sample	11-13 12	NA 10	NA NA	0.483-1.09 0.745	1
pH		N/A	N/A	NA	Range	8.2	7.3-8.9	NA	7.40-8.93	
	pН	NA	NA	NA	Average Range	8.2 2.8-3.2	8.3 NA	NA NA	8.52 1.31-4.36	
Potassium	ppm	NA	NA	NA	Sample	3.0	2.7	NA	2.46	
Sodium	ppm	NA	NA	NA	Range Sample	48-56 52	NA 50	NA NA	32.7-80.4 52.3	
тос	ppm	тт	NA	0.30	Range	1.9-3.1	2.0-3.0	NA NA	NA NA	Various natural and man-made sources
	рріп	- ''	INA	0.30						
N-Nitrosodimethylamine (NDMA)	ppt	NL = 10	3	2	Range D.Wide	ND-3.1	NA NA	NA NA	NA NA	By-product of drinking water
					D.TTIGE	ND	ND	NA	NA	

How to Read this Report

As you read the water quality tables in this report, compare the level of contaminants found in Carlsbad Municipal Water District's water in the "Skinner Plant", "Twin Oaks Valley Plant", and "Desal plant" columns with the standards set for them in the MCL and PHG columns. The Carlsbad Municipal Water District met all drinking water standards in 2019.

The following are key terms to help you understand the standards used to measure drinking water safety.

Maximum Contaminant Level (MCL) The highest level of a contaminant that is allowed in drinking water. Primary MCLs are set as close to the PHGs (or MCLGs) as is economically and technologically feasible. Secondary MCLs are set to protect the odor, taste and appearance of drinking water.

Maximum Contaminant Level Goal (MCLG) The level of a contaminant in drinking water below which there is no known or expected risk to health. MCLGs are set by the U.S. Environmental Protection Agency.

Public Health Goal (PHG) The level of a contaminant in drinking water below which there is no known or expected risk to health. PHGs are set by the California Environmental Protection Agency.

Maximum Residual Disinfectant Level (MRDL) The highest level of a disinfectant allowed in drinking water. There is convincing evidence that addition of a disinfectant is necessary for control of microbial contaminants.

Maximum Residual Disinfectant Level Goal (MRDLG) The level of a drinking water disinfectant below which there is no known or expected risk to health. MRDLGs do not reflect the benefits of the use of disinfectants to control microbial contaminants.

Primary Drinking Water Standard (PDWS) MCLs and MRDLs for contaminants that affect health along with their monitoring and reporting requirements, and water treatment requirements.

Treatment Technique A required process intended to reduce the level of a contaminant in drinking water.

Regulatory Action Level The concentration of a contaminant which, if exceeded, triggers treatment or other requirements that a water system must follow.

This report can be downloaded from www.carlsbadca.gov/ water-quality-report

Abbreviations

ΑI Aggressiveness Index

AL Action Level

CDPH California Department of Public Health

CFE Combined Filter Effluent CFU Colony-Forming Units DBP Disinfection By-Products

DLR Detection Limits for purposes of Reporting

MCL Maximum Contaminant Level MCLG Maximum Contaminant Level Goal

MFL Million Fibers per Liter

MRDI Maximum Residual Disinfectant Level MRDLG Maximum Residual Disinfectant Level Goal

Ν Nitrogen NA Not Applicable ND Not Detected NL Notification Level

NTU Nephelometric Turbidity Units

pCi/L picoCuries per Liter

PHG Public Health Goal

SI

TOC

TON

parts per billion or micrograms per liter (µg/L) ppb parts per million or milligrams per liter (mg/L) ppm parts per quadrillion or picograms per liter (pg/L) ppq ppt parts per trillion or nanograms per liter (ng/L)

RAA Running Annual Average; highest RAA is the highest of all Running Annual Averages calculated as average of all the samples collected

> within a 12-month period Saturation Index (Langelier) **Total Organic Carbon** Threshold Odor Number

TT Treatment Technique is a required process intended to reduce the level

of a contaminant in drinking water

microSiemen per centimeter; or micromho per centimeter (µmho/cm)

Required information for lead

If present, elevated levels of lead can cause serious health problems, especially for pregnant women and young children. Lead in drinking water is primarily from materials and components associated with service lines and home plumbing. Carlsbad Municipal Water District is responsible for providing high quality drinking water, but cannot control the variety of materials used in plumbing components. When your water has been sitting for several hours, you can minimize the potential for lead exposure by flushing your tap for 30 seconds to 2 minutes before using water for drinking or cooking. If you are concerned about lead in your water, you may wish to have your water tested. Information on lead in drinking water, testing methods and steps you can take to minimize exposure is available from the Safe Drinking Water Hotline or at www.epa.gov/safewater/lead. Carlsbad Municipal Water District has complied and meets Lead and Copper standards.

Footnotes

- (a) (Skinner) As a Primary Standard, the turbidity levels of the filtered water were < 0.3 NTU in 95% of the online measurements taken each month and did not exceed 1 NTU for more than one hour.
 - The turbidity levels for grab samples at these locations were in compliance with the Secondary Standard. (Twin Oaks) The turbidity level from the CFE of the membranes shall be < 0.1 NTU in 95% of the measurements taken each month and shall not exceed 1.0 NTU at any time. Turbidity, a measure of the cloudiness of water, is an indicator of treatment performance.
- (b) Total coliform MCLs: No more than 5% of the monthly samples may be total coliform positive. Compliance is based on the combined distribution system sampling. In 2020, 1,560 samples were analyzed with no positive samples. The MCL was not
- (c) E. coli MCL: The occurrence of two consecutive total coliformpositive samples, one of which contains E. coli, constitutes an acute MCL violation. The MCL was not violated.
- (d) Skinner and Twin Oaks were in compliance with all provisions of the State's Fluoridation System Requirements.
- (e) Lead and copper are regulated by Action Levels under the Lead and Copper Rule, which requires water samples to be collected at the consumers' tap. If action levels are exceeded in more than 10% of the samples, water systems must take steps to reduce these contaminants.
- Twin Oaks/Skinner met all provisions of the Stage 1 Disinfectants/ Disinfection By-Products (D/DBP) Rule. Compliance was based on Locational RAA. Average and range for the treatment plant effluent were taken from daily and monthly samples for TTHM and HAA5.
- (g) Twin Oaks running annual average was calculated from quarterly results of monthly and daily samples. Bromate reporting level is 4.2 ppb.
- (h) Chromium VI reporting level is ND, which is below the state DLR of 1 ppb.
- (i) Al <10.0 = Highly aggressive and very corrosive water. Al >12.0 = Non-aggressive water. Al (0.14 - 13.0) = Moderately aggressive water.
- (j) Positive SI index = non-corrosive; tendency to precipitate and/or deposit scale on pipes. Negative SI index = corrosive; tendency to dissolve calcium carbonate.