

2019 CONSUMER CONFIDENCE REPORT

conservation A NEW WAY OF LIFE

CITY OF SOLVANG 1644 OAK STREET SOLVANG, CA 93463 (805) 688-5575 https://www.cityofsolvang.com/ccr2019

2019 Consumer Confidence Report

Water System Name: CITY OF SOLVANG	Report Date: JUNE 2019
· · ·	ts as required by state and federal regulations. This report shows 1 - December 31, 2019 and may include earlier monitoring data.
Este informe contiene información muy importante entienda bien.	sobre su agua potable. Tradúzcalo ó hable con alguien que lo
Type of water source(s) in use: Ground Water (Solv	ang Wells & ID#1 Wells) & Surface Water (CCWA)
Ynez River V	A River Wells; Well 4, 21, 22, & HCA South Upland Wells; Santa Vater Conservation District, Improvement District No. 1 (ID#1) & t Water Authority (CCWA)
Drinking Water Source Assessment information: Source 200	arce Assessments for the City's wells were completed September
Time and place of regularly scheduled board meetings	for public participation: Second & Fourth Monday of each Month at 1644 Oak Street, Solvang, CA @ 6:30 P.M.
For more information, contact: Mike Mathews	Phone: (805) 688-5575
TERMS US	ED IN THIS REPORT
Maximum Contaminant Level (MCL) : The highe level of a contaminant that is allowed in drinking wate Primary MCLs are set as close to the PHGs (or MCLG as is economically and technologically feasibl Secondary MCLs are set to protect the odor, taste, an appearance of drinking water.	 contaminants that affect taste, odor, or appearance of the drinking water. Contaminants with SDWSs do not affect the health at the MCL levels. Treatment Technique (TT): A required process intended to
Maximum Contaminant Level Goal (MCLG): The level of a contaminant in drinking water below whice there is no known or expected risk to health. MCLC are set by the U.S. Environmental Protection Agence (U.S. EPA). Public Health Goal (PHG): The level of a contaminant	contaminant which, if exceeded, triggers treatment or other requirements that a water system must follow. Variances and Exemptions: State Board permission to exceed an MCL or not comply with a treatment technique
 in drinking water below which there is no known of expected risk to health. PHGs are set by the Californ Environmental Protection Agency. Maximum Residual Disinfectant Level (MRDL The highest level of a disinfectant allowed in drinkin water. There is convincing evidence that addition of 	 Level 1 Assessment: A Level 1 assessment is a study of the water system to identify potential problems and determine (if possible) why total coliform bacteria have been found in our water system. Level 2 Assessment: A Level 2 assessment is a very detailed a trudy of the water system to identify potential problems and
disinfectant is necessary for control of microbia contaminants. Maximum Residual Disinfectant Level Gos (MRDLG): The level of a drinking water disinfectant below which there is no known or expected risk health. MRDLGs do not reflect the benefits of the us of disinfectants to control microbial contaminants. Primary Drinking Water Standards (RDWS): MCL	 determine (if possible) why an <i>E. coli</i> MCL violation has occurred and/or why total coliform bacteria have been found in our water system on multiple occasions. ND: not detectable at testing limit ppm: parts per million or milligrams per liter (mg/L) ppb: parts per billion or micrograms per liter (µg/L)
Primary Drinking Water Standards (PDWS) : MCI and MRDLs for contaminants that affect health alor with their monitoring and reporting requirements, an water treatment requirements.	^{1g} ppg : parts per quadrillion or picogram per liter (pg/L)

The sources of drinking water (both tap water and bottled water) include rivers, lakes, streams, ponds, reservoirs, springs, and wells. As water travels over the surface of the land or through the ground, it dissolves naturally-occurring minerals and, in some cases, radioactive material, and can pick up substances resulting from the presence of animals or from human activity.

Contaminants that may be present in source water include:

- *Microbial contaminants*, such as viruses and bacteria, that may come from sewage treatment plants, septic systems, agricultural livestock operations, and wildlife.
- *Inorganic contaminants*, such as salts and metals, that can be naturally-occurring or result from urban stormwater runoff, industrial or domestic wastewater discharges, oil and gas production, mining, or farming.
- *Pesticides and herbicides*, that may come from a variety of sources such as agriculture, urban stormwater runoff, and residential uses.
- Organic chemical contaminants, including synthetic and volatile organic chemicals, that are byproducts of industrial processes and petroleum production, and can also come from gas stations, urban stormwater runoff, agricultural application, and septic systems.
- *Radioactive contaminants*, that can be naturally-occurring or be the result of oil and gas production and mining activities.

In order to ensure that tap water is safe to drink, the U.S. EPA and the State Water Resources Control Board (State Board) prescribe regulations that limit the amount of certain contaminants in water provided by public water systems. State Board regulations also establish limits for contaminants in bottled water that provide the same protection for public health.

Tables 1, 2, 3, 4, 5, and 6 list all of the drinking water contaminants that were detected during the most recent sampling for the constituent. The presence of these contaminants in the water does not necessarily indicate that the water poses a health risk. The State Board allows us to monitor for certain contaminants less than once per year because the concentrations of these contaminants do not change frequently. Some of the data, though representative of the water quality, are more than one year old. Any violation of an AL, MCL, MRDL, or TT is asterisked. Additional information regarding the violation is provided later in this report.

TABLE 1 –	SAMPLING	RESULTS SHOW	ING THE DETECTION O	F COLIFO	RM BACTERIA
Microbiological Contaminants	Highest No. of Detections	No. of Months in Violation	MCL	MCLG	Typical Source of Bacteria
Total Coliform Bacteria	0	0	More than 1 sample in a month with a detection	0	Naturally present in the environment
Fecal Coliform or <i>E. coli</i>	0	0	A routine sample and a repeat sample detect total coliform and either sample also detects fecal coliform or <i>E. coli</i>	0	Human and animal fecal waste
E. coli	0	0	A routine sample and a repeat sample detect total coliform and either sample also detects <i>E. coli</i>		Human and animal fecal waste

TABLE 2	- SAMPL	ING RESU	LTS SHOV	WING THE	DETEC	TION	OF LEAD AND COPPER
Lead and Copper	Sample Date	No. of Samples Collected	90 th Percenti le Level Detected	No. Sites Exceeding AL	AL	PH G	Typical Source of Contaminant
Lead (ppb)	3/29/17	20	8.7	0	15	0.2	Internal corrosion of household water plumbing systems; discharges from industrial manufacturers; erosion of natural deposits
Copper (ppb)	3/29/17	20	620	0	1300	0.3	Internal corrosion of household plumbing systems; erosion of natural deposits; leaching from wood preservatives

	TABLE 3 – SAMPLING RESULTS FOR SODIUM AND HARDNESS										
Chemical or Constituent (and reporting units)	Sample Date	Level Detected	Range of Detections	MCL	PHG (MCLG)	Typical Source of Contaminant					
Sodium (ppm)	2017-2019	63	55-72	none	none	Salt present in the water and is generally naturally occurring					
Hardness (ppm)	2017-2019	599	412-713	none	none	Sum of polyvalent cations present in the water, generally magnesium and calcium, and are usually naturally occurring					

TABLE 4 – DET	ECTION O	F CONTAMIN	ANTS WITH A	PRIMARY	DRINKING	WATER STANDARD
Chemical or Constituent (and reporting units)	Sample Date	Level Detected	Range of Detections	MCL [MRDL]	PHG (MCLG) [MRDLG]	Typical Source of Contaminant
Fluoride (ppm)	2017- 2019	0.20	<0.1-0.3	2	1	Erosion of Natural deposits; water additive which promotes strong teeth
Nitrate (ppm) (as N03)	2017- 2019	5.56	<0.5-17.0	45	45	Runoff & leaching from fertilizer use; sewage; erosion of natural deposits
Nitrate and Nitrite (as N) (ppm)	2017- 2019	1.26	<.1-3.9	10	10	Runoff & leaching from fertilizer use; sewage; erosion of natural deposits
Hexavalent Chromium (ppb)	2017- 2019	<.1	<1-1	10	.02	Discharge from electroplating factories, leather tanneries, wood preservation, chemical synthesis, refractory production, and textile manufacturing facilities; erosion of natural deposits.
Tetrachloroethylene (PCE) (ppb)	2016- 2019	.45	0-0.7	5	N/A	Leaching from PVC pipes: discharge from factories, dry cleaners and auto shops (metal degreasers)
Gross Alpha Activity (pCi/L)	2016- 2019	8.94	3.75-16	15	N/A	Erosion of natural deposits
Uranium (pCi/L)	2016- 2019	7.66	1.3-16.5	20	.5	Erosion of natural deposits
Trihalomethane (TTHM) (ppb)	1/19- 10/19	29.1	14-36	80	N/A	Byproduct of drinking water chlorination
Haloacetic Acid (HA A5) (ppb)	1/19- 10/19	17.6	7-30	60	N/A	Byproduct of drinking water chlorination
Selenium (ppb)	2017- 2019	9.33	<1-23	50	50	Erosion of natural deposits; discharge chemical manufacturers and runoff from livestock lot.

TABLE 5 – DETE	CTION OF	CONTAMINA	NTS WITH A <u>SE</u>	CONDAR	<u>Y</u> DRINKIN	G WATER STANDARD
Chemical or Constituent (and reporting units)	Sample Date	Level Detected	Range of Detections	MCL	PHG (MCLG)	Typical Source of Contaminant
Chloride (ppm)	2017- 2019	76.33	51-117	500	N/A	Runoff/leaching from natural deposits; seawater influence
Odor (units)	2017- 2019	0.06	<.134	3	N/A	Natural occurring materials
Specific conductance (Umhos/cm)	2017- 2019	1353	1120-1590	**2	1	Substance that forms ions when in water; seawater influence
Sulfate (ppm)	2017- 2019	279	203-337	*2	N/A	Runoff/leaching from natural deposits; industrial wastes
Total Dissolved Solids (ppm)	2017- 2019	925	760-1090	1000	N/A	Runoff/leaching from natural deposits

	TABLE 6 – DETECTION OF UNREGULATED CONTAMINANTS											
Chemical or Constituent (and reporting units)	Sample Date	Level Detected	Range of Detections	Notification Level	Health Effects Language							
Boron (ppb)	2017- 2019	250	200-300		Some men who drink water containing boron in excess of the action level over many years may experience reproductive effects based on studies in dogs.							
Vanadium (ppb)	2017- 2019	6.5	<1.0-10		The babies of some pregnant women who drink water containing vanadium in excess of the action level may have an increased risk of developmental effects, based on studies in laboratory animals							

*Any violation of an MCL, MRDL, or TT is asterisked. Additional information regarding the violation is provided later in this report.

Additional General Information on Drinking Water

Drinking water, including bottled water, may reasonably be expected to contain at least small amounts of some contaminants. The presence of contaminants does not necessarily indicate that the water poses a health risk. More information about contaminants and potential health effects can be obtained by calling the U.S. EPA's Safe Drinking Water Hotline (1-800-426-4791).

Some people may be more vulnerable to contaminants in drinking water than the general population. Immuno-compromised persons such as persons with cancer undergoing chemotherapy, persons who have undergone organ transplants, people with HIV/AIDS or other immune system disorders, some elderly, and infants can be particularly at risk from infections. These people should seek advice about drinking water from their health care providers. U.S. EPA/Centers for Disease Control (CDC) guidelines on appropriate means to lessen the risk of infection by *Cryptosporidium* and other microbial contaminants are available from the Safe Drinking Water Hotline (1-800-426-4791).

Lead-Specific Language for Community Water Systems: If present, elevated levels of lead can cause serious health problems, especially for pregnant women and young children. Lead in drinking water is primarily from materials and components associated with service lines and home plumbing. The City of Solvang is responsible for providing high quality drinking water, but cannot control the variety of materials used in plumbing components. When your water has been sitting for several hours, you can minimize the potential for lead exposure by flushing your tap for 30 seconds to 2 minutes before using water for drinking or cooking. [Optional: If you do so, you may wish to collect the flushed water and reuse it for another beneficial purpose, such as watering plants.] If you are concerned about lead in your water, you may wish to have your water tested. Information on lead in drinking water, testing methods, and steps you can take to minimize exposure is available from the Safe Drinking Water Hotline (1-800-426-4791) or at https://www.epa.gov/lead



CENTRAL COAST WATER AUTHORITY POLONIO PASS WATER TREATMENT PLANT WATER QUALITY TABLE COVERING THE REPORTING PERIOD OF JANUARY-DECEMBER 2019

Please see last page for key to abbreviations.

			TREATED	SOURCE			
	State	PHG	State	Range		STATE	
Parameter Units	ts MCL	(MCLG)	DLR	Average	CCWA	WATER	Major Sources in Drinking Water

PRIMARY STANDARDS--Mandatory Health-Related Standards

CLARITY (a)											
Combined Filter Effluen	t NTU	TT=<1 NTU every 4 hours			Range	0.03 - 0.1		NA	Soil runoff		
Turbidity (a)	NIU	TT=95% of	f samples <	0.3 NTU	%	100%		NA			
NORGANIC CHEMICALS											
Aluminum	mg/L	ag/(1 (b) 0.6	0.6	0.05	Range	ND - 0.094	N	ND - 0.31	Erosion of natural deposits; residual from some		
Aluminum	mg/L	1 (b)	0.0		Average	0.056		0.127	surface water treatment processes		
RADIONUCLIDES			-	_							
Gross Alpha Particle	pCi/L	pCi/L 15	(0)	3	Range	ND		5.3	Erosion of natural deposits		
Gross Alpha Particle	poi/L	15	(0)	5	Average	ND		5.3			

DISTRIBUTION SYSTEM MONITORING

r						0.00 0.5		
Total Chlorine Residual	mg/L	MRDL = 4.0	MRDLG =	NA	Range	0.33 - 3.5	NA	Drinking water disinfectant added for treatment
	MINDE 1.0	4.0	1.7.1	Average	2.47	NA	Brinning water defineetant daded for redament	
Total Coliform	5.0% of			Range	0	NA		
Bacteria (c)		monthly	(0)		Average	0	NA	Naturally present in the environment
	samples			Highest	0%	NA		
Total Trihalomethanes				Range	24 - 75	NA		
(d)	ug/L	ug/L 80	NA	(0.5)	Average	45	NA	By-product of drinking water chlorination
(u)					Highest LRAA	47.8	NA	
Haloacetic Acids (d)					Range	7.4 - 25	NA	
	ug/L	60	NA	(1) (e)	Average	15	NA	By-product of drinking water chlorination
					Highest LRAA	15.5	NA	

SECONDARY STANDARDS--Aesthetic Standards

Chloride	mg/L	500 (j)	NA	(1)	Range	13 - 146	11 - 142	Runoff/leaching from natural deposits; seawater
Chionde	mg/∟	500 (J)	N/A	(1)	Average	59	56	influence
Color	ACU	15 (j)	NA	(3)	Range	ND	20	-Naturally occuring organic materials
00101	700	15 ()	IN/A	(3)	Average	ND	20	Naturally occurring organic materials
Corrosivity	SU	non-	NA	(0.1)	Range	12	12	
(Aggresivity Index) (i)	00	corrosive	TW/	(0.1)	Average	12	12	
Manganese, Total	ug/L	50 (j)	NA	(2)	Range	ND	8.8	
	50 (J)	1.07.1	(2)	Average	ND	8.8		
Odor Threshold TON	3 (j)	NA	(1)	Range	ND	2	Naturally occuring organic materials	
	TON	u ()	TW/	(1)	Average	ND	2	Naturally occurring organic materials
Specific Conductance	uS/cm	1600 (j)	NA	NA	Range	138 - 762	131 - 691	Substances that form ions when in water;
	uo/cm	1000 (j)		INA.	Average	403	353	seawater influence
Sulfate	mg/L	500 (j)	NA	(0.5)	Range	46	34	Runoff/leaching from natural deposits; industrial
Suilate	mg/∟	500 (J)	11/24	(0.3)	Average	46	34	wastes
Total Dissolved Solids	ma/l	1000 (j)	NA	(10)	Range	260	250	Runoff/leaching from natural deposits
(TDS) mg/L	mg/∟	1000 (j)	11/74	(10)	Average	260	250	
Turbidity (Monthly) (a)	NTU	5 (j)	NA	(0.1)	Range	ND - 0.12	0.38 - 55	Soil runoff
r arbiarty (montility) (a)	1110	5()	11/74	(0.1)	Average	0.05	3.39	

ADDITIONAL PARAMETERS (Unregulated)

2-Methylisoborneol	ng/L	NA	NA	(1)	Range Average	ND - 1 0.2	2 - 8 3.8	An organic compound mainly produced by blue- green algae (cyanobacteria)
Alkalinity (Total) as	mg/L	NA	NA	(2)	Range	30 - 80	28 - 86	Runoff/leaching from natural deposits; seawater
CaCO3 equivalents	ilig/L	NA	INA.	(2)	Average	56	59	influence
Calcium mg/L NA	NA	NA	(1)	Range	19	18	Runoff/leaching from natural deposits; seawater	
	INA			Average	19	18	influence	
Geosmin	ng/L	NA	NA	(4)	Range	ND - 6	2 - 8	An organic compound mainly produced by
Geosmin ng/L NA	NA	NA	(1)	Average	2.8	3.8	bacterial growth in surface water	
Hardness (Total) as	rdness (Total) as mg/L NA NA	NA	(0)	Range	26 - 144	28 - 144	Leaching from natural deposits	
CaCO3 mg/L NA	NA	(3)	Average	82	82	Leaching non natural deposits		

Heterotrophic Plate	CFU/mL	TT	NA	NA	Range	0 - 2	NA	-Naturally present in the environment
Count (f)					Average	0	NA	
Magnesium	mg/L	NA	NA	(0.1)	Range	12	11	Runoff/leaching from natural deposits; seawater
Maynesium	iiig/L	11/4	11/4	(0.1)	Average	12	11	influence
рН	SU	NA	NA	(0.1)	Range	7.7 - 8.7	7.5 - 9.3	Runoff/leaching from natural deposits; seawater
	00				Average	8.4	8.4	influence
Potassium	mg/L	NA	NA	(1)	Range	3.1	3.1	Runoff/leaching from natural deposits; seawater
	iiig/E				Average	3.1	3.1	influence
Sodium	mg/L	NA	NA	(1)	Range	58	50	Runoff/leaching from natural deposits; seawater
	iiig/L				Average	58	50	influence
Total Organic Carbon	mg/L	TT N	NA	(0.3)	Range	1.5 - 3	2.6 - 5.4	Various natural and man made sources
(TOC) (g)	iiig/L	11	NA	(0.3)	Average	1.9	3.2	vanous natural and mail fildue sources

ABBREVIATIONS AND NOTES

Footnotes:

- (a) Turbidity (NTU) is a measure of the cloudiness of the water and it is a good indicator of the effectiveness of our filtration system. Monthly turbidity values are listed in the Secondary Standards section.
 (b) Aluminum has a Secondary MCL of 0.2 ppm.
- (c) Total coliform MCLs: Systems that collect ≥40 samples/month no more than 5.0% of the monthly samples may be Total Coliform positive. Systems that collect <40 samples per month no more than 1 positive sample per month may be Total Coliform positive. Fecal coliform/E. coli MCLs: The occurrence of 2 consecutive Total Coliform positive samples, one of which contains fecal coliform/E. coli, constitutes an acute MCL violation.</p>
- (d) Compliance based on the running quarterly annual average of distribution system samples.
 (e) Monochloroacetic Acid (MCAA) has a DLR of 2.0 ug/L while the other four Haloacetic Acids
- have DLR's of 1.0 ug/L.
- (f) Pour plate technique
- (g) TOCs are taken at the treatment plant's combined filter effluent.
- (h) State MCL is 45 mg/L as NO3, which equals 10 mg/L as N.
- (i) AI ³ 12.0 = Non-aggressive water
 AI (10.0 11.9) = Moderately aggressive water
 AI £ 10.0 = Highly aggressive water
 Reference: ANSI/AWWA Standard C400-93 (R98)
- (j) Secondary MCL

Abbreviations

ACU = Apparent Color Units CCWA = Central Coast Water Authority CFU/ml = Colony Forming Units per milliliter DLR = Detection Level for purposes of Reporting MCL = Maximum Contaminant Level MCLG = Maximum Contaminant Level Goal MRDL = Maximum Residual Disinfectant Level MRDLG = Maximum Residual Disinfectant Level Goal NA = Not Applicable ND = Non-detected above detection limit (DLR) NTU = Nephelometric Turbidity Units pCi/L = PicoCuries per liter . PHG = Public Health Goal ppb = parts per billion, or micrograms per liter (µg/L) ppm = parts per million, or milligrams per liter (mg/L) TON = Threshold Odor Number TT = Treatment Technique LRAA = Locational Running Annual Average

Parameter PRIMARY STANDARD CLARITY Combined Filter Effluent Turbidity ^a INORGANIC CHEMICALS Aluminum ^b Arsenic Chromium (Total Cr) Fluoride Nickel Nitrate (as Nitrogen) RADIONUCLIDES	Units SMan NTU ppm ppb ppb ppb	TT=<1 N	PHG (MCLG) alth-Relat TU every 4 I f samples <0 0.6 0.004 (100)	hours	Range Average Idards Range % Range Average	Drinking Wa State Water 0.03 - 0.1 100%	Ground Water NA NA	Major Sources in Drinking Water
PRIMARY STANDARD CLARITY Combined Filter Effluent Turbidity ^a INORGANIC CHEMICALS Aluminum ^b Arsenic Chromium (Total Cr) Fluoride Nickel Nitrate (as Nitrogen)	SMan NTU ppm ppb ppb ppm	MCL TT=<1 N TT=95% of 1 (b) 10 50	(MCLG) alth-Relat TU every 4 I f samples <0 0.6 0.004	DLR ted Stan	Average Idards Range % Range	Water 0.03 - 0.1	Water	
CLARITY Combined Filter Effluent Turbidity ^a INORGANIC CHEMICALS Aluminum ^b Arsenic Chromium (Total Cr) Fluoride Nickel Nitrate (as Nitrogen)	NTU ppm ppb ppb	TT=<1 N TT=95% of 1 (b) 10 50	alth-Relat TU every 4 I f samples <0 0.6 0.004	hours 0.3 NTU 0.05	Range % Range			
CLARITY Combined Filter Effluent Turbidity ^a INORGANIC CHEMICALS Aluminum ^b Arsenic Chromium (Total Cr) Fluoride Nickel Nitrate (as Nitrogen)	NTU ppm ppb ppb	TT=<1 N TT=95% of 1 (b) 10 50	TU every 4 I f samples <0 0.6 0.004	hours 0.3 NTU 0.05	Range % Range			Soil runoff
Combined Filter Effluent Turbidity ^a INORGANIC CHEMICALS Aluminum ^b Arsenic Chromium (Total Cr) Fluoride Nickel Nitrate (as Nitrogen)	ppm ppb ppb ppm	TT=95% of 1 (b) 10 50	0.6 0.004	0.3 NTU 0.05	% Range			Soil runoff
Effluent Turbidity ^a INORGANIC CHEMICALS Aluminum ^b Arsenic Chromium (Total Cr) Fluoride Nickel Nitrate (as Nitrogen)	ppm ppb ppb ppm	TT=95% of 1 (b) 10 50	0.6 0.004	0.3 NTU 0.05	% Range			Soil runoff
INORGANIC CHEMICALS Aluminum ^b Arsenic Chromium (Total Cr) Fluoride Nickel Nitrate (as Nitrogen)	ppm ppb ppb ppm	1 (b) 10 50	0.6	0.05	Range	100%	NA	
Aluminum ^b Arsenic Chromium (Total Cr) Fluoride Nickel Nitrate (as Nitrogen)	ppb ppb ppm	10 50	0.004		Ū			
Aluminum ^b Arsenic Chromium (Total Cr) Fluoride Nickel Nitrate (as Nitrogen)	ppb ppb ppm	10 50	0.004		Ū			
Arsenic Chromium (Total Cr) Fluoride Nickel Nitrate (as Nitrogen)	ppb ppb ppm	10 50	0.004		Average	ND - 0.094	ND	Residue from water treatment process;
Chromium (Total Cr) Fluoride Nickel Nitrate (as Nitrogen)	ppb ppm	50		2	-	0.056	ND	Erosion of natural deposits
Fluoride Nickel Nitrate (as Nitrogen)	ppm		(100)		Range	ND	ND - 3	Erosion of natural deposits; orchard runoff; from
Fluoride Nickel Nitrate (as Nitrogen)	ppm		(100)		Average Range	ND ND	1.1 ND - 18	glass/electronics production wastes Erosion of natural deposits; steel,
Nickel Nitrate (as Nitrogen)		2	· · · · /	10	Average	ND	6.0	pulp mills, and chrome plating wastes
Nickel Nitrate (as Nitrogen)		Z	1	0.1	Range	ND	ND - 0.30	Erosion of natural deposits;
Nitrate (as Nitrogen)	ppb		1	0.1	Average	ND	0.17	water additive for tooth health
		100	12	10	Range	ND	ND - 11	Erosion of natural deposits; discharge from
					Average	ND	1.6	metal factories Runoff and leaching from fertilizer use; leaching
	ppm	10	10	0.4	Range	NA	ND - 2.7	from septic tanks and sewage; erosion of natural
RADIONUCLIDES	ppm	10	10	0.4	Average	NA	0.9	deposits
RADIONOCLIDES								
1					Range	ND	ND - 11	Γ
Gross Alpha ^c	pCi/L	15	NA	3	Average	ND	2.5	Erosion of natural deposits
d					Range	NC	2.5 - 5.6	
Uranium ^d	pCi/L	20	0.5	1	Average	NC	4.1	Erosion of natural deposits
					Range	NC	ND - 0.093	
Radium 226 ^e	pCi/L	5	NA	3	Average	NC	0.05	Erosion of natural deposits
SECONDARY STAND	ARDS	Aesthetic	Standard	s				
Aluminum	ppm	0.2	NA	0.05	Range Average	ND - 0.094 0.056	ND ND	Residue from water treatment process; Erosion of natural deposits
					Range	13 - 146	30 - 54	Runoff/leaching from natural deposits;
Chloride	ppm	500	NA		Average	59	40.4	seawater influence
Color	ACU	15	NA		Range	ND	ND - 3	Naturally-occurring organic materials
Corrosivity					Average	ND 12	0.3	
, , , , , , , , , , , , , , , , , , ,	none	non-	NA		Range	12	12.1 - 12.4	Balance of hydrogen, carbon, & oxygen in water, affected by temperature & other factors
(Aggresive Index)		corrosive			Average	ND		Leaching from natural deposits;
Iron	ppb	300	NA	100	Range Average	ND	33	industrial wastes
		50		00	Range	ND	ND - 23	
Manganese	ppb	50	NA	20	Average	ND	2.9	Leaching from natural deposits
Odor Threshold	TON	3	NA	1	Range	ND	1 - 3	Naturally-occurring organic materials
		•		•	Average	ND	1.2	, , , , , , , , , , , , , , , , , , , ,
Specific Conductance	µmho/	1600	NA		Range	138 - 762 403	730 - 1100 880	Substances that form ions when in water; seawater influence
	cm				Average Range	403 46	30 - 270	Runoff/leaching from natural deposits;
Sulfate	ppm	500	NA	0.5	Average	40	161	industrial wastes
Total Dissolved	nnm	1000	NA		Range	260	460 - 710	Runoff/leaching from natural deposits;
Solids (TDS)	ppm	1000	INA		Average	260	561	
Lab Turbidity (ID#1)	NTU	5	NA		Range	ND - 0.12	ND - 1.4	Soil erosion/runoff
Turbidity (State Water)	_	-			Average	0.05	0.31	
ADDITIONAL PARAME	TERS ((Unr <u>egulat</u>	ed)					
					Demo	20 00	060 000	Dunoff/loophing from a translater "
Alkalinity (Total) as CaCO₃ equivalents	ppm	NA	NA		Range Average	30 - 80 56	260 - 290 281	Runoff/leaching from natural deposits; seawater influence
					Range	NC	110 - 320	Runoff/leaching from natural deposits;
Boron	ppb	NA	NL=1,000	100	Average	NC	201	wastewater, and fertilizers/pesticides.
Calcium	nnm	NA	NA		Range	19	46 - 100	Runoff/leaching from natural deposits;
Calcium	ppm	INA	INA		Average	19	71.3	seawater influence
Chromium, Hexavalent ^g	ppb	NA	0.02	1.0	Range	NC	ND - 13	Discharges from industrial manufacturers; erosion
					Average	NC	6.2	of natural deposits
Geosmin	ng/L	NA	NA	(1)	Range Average	ND - 6 2.8	NC NC	An organic compound mainly produced by blue-green algae (cyanobacteria)
Geosiniin							300 - 490	
Geosmin Hardness (Total) as	ppm	NA	NA		Range	26 - 144	300 - 490	Leaching from natural deposits

2019 Annual Water Quality Report - Santa Ynez River Water Conservation District, ID#1

					Drinking Wa	ater Source		
Parameter	Units	State MCL	PHG (MCLG)	State DLR	Range Average	State Water	Ground Water	Major Sources in Drinking Water
Heterotrophic Plate	CFU/mL	тт	NA		Range	0 - 2	NA	Naturally present in the environment
Count ^h					Average	0	NA	
Magnesium	ppm	NA	NA		Range	12	49 - 58	Runoff/leaching from natural deposits; seawater influence
Magnesium	ppm				Average	12	53	
2-Methylisoborneol (MIB)	ng/L	NA	NA	NA	Range	ND - 1	NC	An organic compound mainly produced by
					Average	0.2	NC	blue-green algae (cyanobacteria)
рН	pH Units	NA	NA		Range	7.7 - 8.7	7.47 - 7.88	Runoff/leaching from natural deposits;
					Average	8.4	7.6	seawater influence
Potassium	ppm	NA	NA		Range	3.1	2.0 - 2.3	Runoff/leaching from natural deposits;
					Average	3.1	2.2	seawater influence
Sodium	ppm	NA	NA		Range	58	38 - 52	Runoff/leaching from natural deposits;
Soulum					Average	58	45	seawater influence
Total Organic Carbon		TT	NIA	0.30	Range	1.5 - 3	NA	
(TOC) ⁱ	ppm	11	TT NA		Average	1.9	NA	Various natural and manmade sources.
Vanadium	nnh	NA	NL=50	3	Range	NC	3.3 - 25	Leaching from natural deposits;
	ppb				Average	NC	11	industrial wastes

Distribution System Water Quality

ORGANIC CHEMICALS

					Range	24 - 75	8.8 - 37.7		
Total Trihalomethanes ^j	ppb	80	NA	NA	Highest	47.8	28.2	By-product of drinking water chlorination	
					LRAA	47.0	20.2		
					Range	7.4 - 25	ND - 16.9		
Haloacetic Acids	ppb	60	NA	1,2 ^k	Highest	15.5	8.9	By-product of drinking water chlorination	
					LRAA	15.5	0.9		
DISINFECTION									
Total chlorine residual		MRDL =	MRDLG =		Range	0.33 - 3.5		Measurement of the disinfectant	
CCWA Distribution	ppm	4.0	4.0		Average	2.47		used in the production of drinking water	

Range

Average

--

Abbrevations and Notes

Free/total chlorine residual

Footnotes:

ID#1 Distribution

(a) Turbidity (NTU) is a good indicator of the effectiveness of a filtration system. Monthly turbidity values for State Water are listed in the Secondary Standards section.

ppm

(b) Aluminum has a Secondary MCL of 0.2 ppm.

MRDL =

4.0

MRDLG =

4.0

- (c) Gross alpha particle activity monitoring required every nine years for State Water; more frequent monitoring is required for some groundwater based on detected levels. Reported average and range are from most recent sampling of all supply wells.
- (d) Uranium monitoring is dependent on measured gross alpha particle activity.
- (e) The MCL for radium is based on a combined total of radium 226 and radium 228.
- (f) $AI \ge 12.0$ = Non-aggressive water
 - AI (10.0 11.9) = Moderately aggressive water
 - $AI \leq 10.0 = Highly aggressive water$
 - Reference: ANSI/AWWA Standard C400-93 (R98)
- (g) There is currently no MCL for Hexavalent Chromim. The previous MCL of 10.0 ppb was withdrawn on September 11, 2017.
- (h) Pour plate technique -- monthly averages.
- (i) TOCs are taken at the State Water treatment plant's combined filter effluent.
- (j) Compliance based on the LRAA of distribution system samples. Values reported are the range of all 2019 sample results and highest locational running annual average.
- (k) Monochloroacetic Acid (MCAA) has a DLR of 2.0 ug/L while the other four Haloacetic Acids have DLR's of 1.0 ug/L.

Abbreviations

14

- ACU = Apparent Color Units
- CCWA = Central Coast Water Authority
- CFU/ml = Colony Forming Units per milliliter
- DLR = Detection Limit for the Purpose of Reporting

0.29 - 2.85 Measurement of the disinfectant

used in the production of drinking water

- ID#1 = Santa Ynez River Water Conservation District,
 - Improvement District No.1
- LRAA Locational Running Annual Average
- NA = Not Applicable
- NC = Not Collected
- ND = Non-detect
- ng/L = nanograms per liter
- NI = Notification I evel
- NTU = Nephelometric Turbidity Units
- pCi/L = PicoCuries per liter
- ppb = parts per billion, or micrograms per liter (μ g/L)
- ppm = parts per million, or milligrams per liter (mg/L)
- SI = saturation index
- TON = Threshold Odor Number
- µmho/cm = micromhos per centimeter

Analytical Results

The following summary table of analytical results confirms that water served by the District met or exceeded all water quality standards during the 2019 reporting period. The table lists the range and average concentrations of the drinking water contaminants (as well as other water quality constituents) that were detected during the most recently required sampling for each source and constituent listed. Also listed are results of the District's required distribution system sampling. It is worth noting that chemicals not detected are not included in the report. Additionally, DDW sampling requirements allow for source monitoring of certain contaminants less than once per year because the concentrations of these contaminants do not vary significantly from year to year. Therefore, some of the data listed in the tables, though representative of the source water quality, are more than a year old.

City of Solvang Conservation Efforts

The City of Solvang has downgraded to Stage 1 Drought Regulations. For a full list of the regulations, please see: www.cityofsolvang.com

Conservation Programs

□ Landscape Rebate For more information on these programs, please contact the City of Solvang at 805-688-5575

Water Wise Facts

□ 1 Unit of water on your water bill = One Hundred Cubic Feet (1 HCF)

□ 1 Unit = 1 HCF = 100 Cubic Feet = 748 gallons

□ The State of California Department of Water Resources has determined the minimum quantity of water for health & safety purposes is 50/gallons per person per day.

□ For a family of four, 50/gallons per person per day = 8.3 Units/month.

Additional Resources

Waterwise Santa Barbara, www.waterwisesb.org

ABBREVIATIONS AND NOTES

Footnotes:

- (a) Turbidity (NTU) is a measure of the cloudiness of the water and is a good indicator of the effectiveness of a filtration system. Monthly turbidity values for State Water are listed in the Secondary Standards section.
- (b) Aluminum has a Secondary MCL of 200 ppb.
- (c) Gross alpha particle activity monitoring required every nine years for State Water; more frequent monitoring is required for some groundwater based on detected levels. Reported average represents highest running source average.
- (d) Uranium monitoring is dependent on measured gross alpha particle activity.
- (e) Pour plate technique -- monthly averages.
- (f) TOCs are taken at the State Water treatment plant's combined filter effluent.
- (g) Total coliform MCLs: No more than 5.0% (State Water) or 1 sample (ID#1) of the monthly samples may be Total Coliform positive. All required follow-up and confirmation samples collected in response to each of the positive Total Coliform samples were absent for Total Coliform.
- (h) Compliance based on the running quarterly annual average of distribution system samples. Values reported are range of all sample results and highest running annual average.
- (j) Monochloroacetic Acid (MCAA) has a DLR of 2.0 ug/L while the other four Haloacetic Acids have DLR's of 1.0 ug/L.

CCWA = Central Coast Water Authority

CFU/ml = Colony Forming Units per milliliter

- ID#1 = Santa Ynez River Water Conservation District, Improvement District No.1
- NA = Not Applicable
- NC = Not Collected
- NL = Notification Level
- NTU = Nephelometric Turbidity Units pCi/L = PicoCuries per liter
- pCI/L = PICOCUTIES per Inter

ppb = parts per billion, or micrograms per liter ($\mu g/L$) ppm = parts per million, or milligrams per liter (mg/L)

SI = saturation index

µmho/cm = micromhos per centimeter, (unit of specific conductance of water)

